

### **PRODUCT DATA SHEET**

## EMERGENCY INSTANT REPAIR

# Thompson's Emergency Instant Repair is a specially formulated, sprayable mastic, for emergency repairs to leaking pipes & guttering.

#### **COMPOSITION**

A solution of mineral rubber, asphalt and binder in mixed solvents, packaged in an aerosol.

#### **PROPERTIES**

Colour - Black.

VOC Content-Very High (>50%w/v) Appearance - Aerosol product containing a viscous liquid. Odour - Characteristic of tar.

#### AREAS OF APPLICATION

Suitable for use on leaking roofs, guttering, pipes & drains.

#### **PREPARATION PROCEDURE**

Give the surface a scrub with a stiff bristle brush to remove any dust, dirt or algae. Give the area of repair a light sand.

#### APPLICATION

Give the can a really good shake until you can hear the mixing balls starting to rattle. Continue to shake the tin for a further minute. For small cracks & holes: Hold the aerosol 45-60cm away from the area of repair. Spray until the whole area is covered. For larger areas of repair: Use the scrim bandage to reinforce the repair. Spray a first coat over the damaged area. Embed the bandage into the coating and apply atleast 3 more heavy coats.

#### CLEAN UP

Hold the can upside down and spray for 3 seconds to clear the nozzle.

#### COVERAGE

A 450 g tin will cover approximately 0.2 m<sup>2</sup>. Coverage is dependent of thickness of the applied coating.

#### FLAMMABILITY

Flash point 8°C. Highly flammable.

Keep away from sources of ignition - no smoking.

#### **STORAGE**

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Store upright and carefully reseal partly used containers.

#### **HEALTH AND SAFETY**

Observe and follow all warnings and instructions for use shown on the pack.

Specific health and safety data sheets are available on request.

#### SUPPL

Obtainable from DIY outlets and builders' merchants.



**SIZES** 450g.

#### LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should be followed.

#### **INFORMATION AND SERVICE**

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

#### DATA SHEETS

Data sheets on other Thompson's products are available on request from our Technical Services Department.

Sherwin-Williams Diversified Brands Ltd has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Sherwin-Williams Diversified Brands Ltd. operate an Environmental Management System that complies with the requirements of BS 7750:1994, Certificate No. EMS 35924. Sherwin-Williams Diversified Brands Ltd. has achieved Investors in People certification, (certificate number 59586).

© Sherwin-Williams Diversified Brands Ltd, Thorncliffe Park, Chapeltown, Sheffield S35 2YP

Tel: (0114) 240 9469 (Technical Services) (0114) 246 7171 (Main Switchboard) Fax: (0114) 245 5629 Email: enquiry@thompsonsweatherproofing.co.uk Web: www.thompsonsweatherproofing.co.uk

Thompsons is a Registered Trademark of the Sherwin-Williams Company. JANUARY, 2009 ISSUE 1