

## EMERGENCY LEAK FIX

**Thompson's Emergency Leak Fix is a clear flexible sealant for use on leaking gutters, pipes and weather damage to doors and windows. It can be applied direct to damp surfaces and over painted.**

### COMPOSITION

Essentially a resin solution in mixed solvents.

### PROPERTIES

Appearance – Colourless viscous liquid.  
Odour – Characteristic. Organic solvents.  
VOC content- High (25-50% w/v)  
Highly Flammable.  
Immiscible with water.

### AREAS OF APPLICATION

Suitable for use on wood, plastic, glass, upvc, brick, stone, roof felt & tiles.

### PREPARATION

Use a stiff bristle brush to remove any dust, dirt or algae. Give the area a light sand.

### APPLICATION

Cut the nozzle at a 45 degree angle to a width matching the gap you're going to seal. Fit the cartridge into a standard sealant gun. Apply slowly and evenly at an angle to the repair, making sure it covers both side of the repair. If you're joining gutters, apply sealant to both surfaces and press them together. Smooth down with a wetted spatula. The product may remain tacky after a few hours of application, so don't touch it.

### COVERAGE

Approximately 11 metres using a 6mm bead of sealant.

### DRYING TIME

Curing time will vary with depth of repair.  
Low temperatures and high humidity will lengthen curing times.

### CLEAN UP

All equipment should be cleaned using white spirit.

### IMPORTANT NOTES

Apply in accordance with the coverage guidelines otherwise product performance will be reduced.

### STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition and direct sunlight.  
Carefully reseal partly used containers. Do not store near foodstuffs. Protect from frost.  
The shelf life of the product in airtight containers is at least two years.

### HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.  
Specific health and safety data sheets are available on request.

### FLAMMABILITY

Highly Flammable.  
Flash point <210C.

### SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

### SIZES

310ml.

### DISPOSAL

Don't empty any left over product into drains or watercourses.  
Your local authority may have special ways to get rid of waste coatings.

### LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should be followed.

### INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

### DATA SHEETS

Data sheets on other Thompson's Products are available on request from our Technical Services Department.

