

ALUMINIUM SOLAR PAINT

Thompson's Aluminium Solar Paint is a light and heat reflective paint suitable for application to bituminous roofing substrates which prolongs the life of roof coatings.



THOMPSON'S ALUMINIUM SOLAR PAINT:

- Provides protection against sun and weather
- Light and heat reflective paint
- Dries to a bright silvery finish

TECHNICAL DATA

Form	Liquid
Storage Life	12 Months unopened stored between 5°C and 25°C in original containers
Flashpoint	38°C

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Thompson's Sales Representative prior to writing specifications on this product.

SURFACE PREPARATION

Surfaces should be clean, dry and free from dust and debris. Existing bitumen coating should be allowed to weather for at least 10 days and preferably a few weeks before the application of Thompson's Aluminium Solar Paint.

APPLICATION

Stir thoroughly before use. Note: The appearance of a silver film on the surface of the paint after a brief period of stirring does not signify that the paint is thoroughly uniform. It is advisable to stir for several minutes to ensure complete dispersion.

Apply by brush or spray. If brushed, do not apply too thickly as this could cause staining, also do not brush excessively as this could cause softening of the substrate.

It is recommended that two coats of Thompson's Aluminium Solar Paint are applied to the surface, the first being allowed to dry completely before application of the second. The presence of moisture on the surface or rainfall before Thompson's Aluminium Solar Paint has dried can also cause staining.

COVERAGE

Approximately 10m² per litre per coat.

CLEANING

Tools may be cleaned with white spirit. Minor spillages should be wiped off surfaces before the paint has dried. Major spillages should be mopped up immediately with an inert, absorbent material, such as sand, and disposed of in accordance with local regulations.

PACKAGING

Sizes:
5L & 25L

HEALTH AND SAFETY

Thompson's Aluminium Solar Paint is based on flammable solvents and appropriate protective equipment should be worn to avoid skin and eye contact and breathing fumes. Keep away from naked flames. Do not smoke. For further information please refer to Health and Safety data sheets available on request.

TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact Thompson's Technical Service.

IMPORTANT NOTE The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Thompson's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Thompson's sole warranty is that the product will meet the Thompson's sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Thompson's specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Thompson's disclaims liability for any incidental or consequential damages.