

# CONCRETE DUSTPROOFER & HARDENER

**Thompson's Concrete Dustproofer & Hardener is used for hardening and dustproofing old and new concrete floors, screeds and paving in factories, garages and domestic dwellings. When applied to a concrete floor surface the solution undergoes a chemical reaction with the free lime in the concrete to form a denser and harder surface with greatly increased resistance to abrasion.**



#### THOMPSON'S CONCRETE DUST PROOFER & HARDENER:

- Hardens and dustproofs all concrete surfaces
- For internal and external use

#### TECHNICAL DATA

Form	Liquid
Storage Life	12 Months stored between 5°C and 25°C in original containers

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Thompson's Sales Representative prior to writing specifications on this product.

#### SURFACE PREPARATION

NOTE: new concrete must be at least 14 days old before treatment.

All surface must be free of surface dirt, grease, oil and any other contaminant and must be swept or vacuumed. It is advisable to thoroughly wash and dry old concrete before application and to treat a small test area first.

#### APPLICATION

Pour Thompson's Concrete Dustproofer & Hardener over the concrete surface and spread evenly with a brush or squeegee. Work well into the surface.

Allow 24 hours between coats. After the second coat wash or hose the surface down with clean water to remove any dust or surplus Thompson's Concrete Dustproofer & Hardener.

Extremely dusty surfaces may need three applications.

#### COVERAGE

Average coverage 3-6m<sup>2</sup> per 1 litre.

#### CLEANING

Clean all material and tools with water after use.

#### PACKAGING

Sizes: 5L & 25L

#### LIMITATIONS

In some instances the use of Thompson's Concrete Dustproofer & Hardener will result in a sealed surface that will not accept a subsequent floor paint.

Thompson's Concrete Dustproofer & Hardener should only be used on cement based products. It is not suitable for painting over brick or similar materials.

Thompson's Concrete Dustproofer & Hardener will not make good broken or disintegrating concrete.

Hard compacted, very dense or power floated surfaces may not have sufficient porosity to allow effective penetration of Thompson's Concrete Dustproofer & Hardener.

#### HEALTH AND SAFETY

Thompson's Concrete Dustproofer & Hardener is irritant. Avoid contact with skin and eyes. For further information please refer to Health and Safety data sheets available on request.

#### TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact Thompson's Technical Service.

**IMPORTANT NOTE** The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Thompson's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Thompson's sole warranty is that the product will meet the Thompson's sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Thompson's specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Thompson's disclaims liability for any incidental or consequential damages.