

FAST SET CEMENT



Thompson's Fast Set Cement is ideal for making permanent repairs to stone, brick, concrete and render.

THOMPSON'S FAST SET CEMENT:

- Sets in 20 minutes for fast repairs
- For permanent repairs to stone, brick, concrete & render

TECHNICAL DATA

Form	Powder
Storage Life	6 Months unopened stored between 5°C and 25°C in original containers, contains Chromium

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Thompson's Sales Representative prior to writing specifications on this product.

SURFACE PREPARATION

All surfaces must be sound and free from all traces of loose material, laitance, oil, dirt and grease. Porous surfaces should be pre-wetted, particularly in hot weather. Avoid ponding water.

APPLICATION

Mix 1kg with approximately 250mls of water. Mix quickly and use straight away.

Keep repair damp for 24 hours after setting by covering it with a damp cloth or newspaper.

For wide cracks mix 1 part Thompson's Fast Set Cement to 3 parts clean dry sharp sand.

CLEANING

Clean all equipment with water immediately after use.

PACKAGING

Size: 3kg

LIMITATIONS

For thicker applications, crosshatch surface and leave for 2 hours before application of a second layer. Maximum thickness in a single layer is 50mm.

HEALTH AND SAFETY

Thompson's Fast Set Cement is irritant wear suitable protective clothing. Avoid contact with skin and eyes. For further information please refer to Health and Safety data sheets available on request.

TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact Thompson's Technical Service.

IMPORTANT NOTE The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Thompson's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Thompson's sole warranty is that the product will meet the Thompson's sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Thompson's specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Thompson's disclaims liability for any incidental or consequential damages.