

## PRODUCT DATA SHEET

# LIQUID CEMENT COLOUR

Thompson's Liquid Cement Colour is a high quality pigment dispersion which produces a permanent colour in concrete, mortars, floors and renders. The liquid disperses easily into the mix to give a uniform shade for each mix batch.

### THOMPSON'S LIQUID CEMENT COLOUR:

- · High quality liquid dispersion
- Delivers permanent colour in concrete, mortar, floors and render
- · Delivers a uniform shade to each mix batch
- · Conforms to BS EN 12878

#### **TECHNICAL DATA**

Form	Liquid
Storage Life	12 Months unopened stored between 5°C and 25°C in original containers
Dosage	up to 5% on cement content by weight

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Thompson's Sales Representative prior to writing specifications on this product.

#### APPLICATION

Always shake container before use as product can settle. Liquid colour can be added to the dry mix or gauging water at the addition rate of up to 2.5L per 50kg of cement in the mix.

Variations of shade are dependant on usage i.e. types of aggregates and cement used. Trial batches should be carried out to obtain shade required.

#### PACKAGING

Size & Colour: 1L Black

#### LIMITATIONS

Thompson's Liquid Cement Colour can not be used as a surface stain and must always be incorporated into the cement based mix.

#### **HEALTH AND SAFETY**

Thompson's Liquid Cement Colour is not classified as hazardous, but prolonged contact may cause irritation. Please refer to Health and Safety data sheets available on request.



#### **TECHNICAL SERVICE**

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact Thompson's Technical Service.

IMPORTANT NOTE The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Thompson's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Thompson's sole warranty is that the product will meet the Thompson's sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Thompson's specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Thompson's disclaims liability for any incidental or consequential damages.

Sherwin-Williams Diversified Brands Ltd operates a Quality Management System that complies with the requirements of ISO 9000:2008 (Certificate No. FM 01669). Sherwin-Williams Diversified Brands Ltd operates an Environmental Management System that complies with the requirements of ISO 14001:2004 (Certificate No. EMS 35924).

Sherwin-Williams Diversified Brands Ltd, Thorncliffe Park, Chapeltown, Sheffield, S35 2YP

Tel: 01752 334350 Email: enquiry@thompsonsweatherproofing.co.uk Web: thompsonsweatherproofing.co.uk

Thompson's is a registered trademark of the Sherwin-Williams Company. April, 2016 Issue 1