

# MOULD RELEASE AGENT

**Thompson's Mould Release Agent is formulated for application onto timber, plywood, steel and plastic mould and formwork before casting concrete.**



#### THOMPSON'S MOULD RELEASE AGENT:

- Excellent coverage
- Controls hydration of cement
- Protects steel from rust
- Apply onto timber, plywood, steel, plastic moulds & framework
- Ready to use

#### TECHNICAL DATA

Form	Liquid
Storage Life	12 Months unopened stored between 5°C and 25°C in original containers

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Thompson's Sales Representative prior to writing specifications on this product.

#### SURFACE PREPARATION

Ensure all surfaces are clean, dry and sound.

#### APPLICATION

Apply Thompson's Mould Release Agent undiluted by spray, brush or roller ensuring a thin even coverage before each casting.

Due to porosity new and untreated tubes should be coated with Thompson's Mould Release Agent at least 36 hours before being used. A second application should then be made before using for the first time.

Do not apply excessive amounts of release oil so that it is running down the mould, as this could be detrimental and cause damage to the edge detail.

#### COVERAGE

Approximately 10 – 15 sq. metres per litre.

#### CLEANING

Any excess material in the bottom of the moulds should be mopped up with a clean cloth prior to the placement of concrete. Clean tools and equipment with white spirit immediately after use.

#### PACKAGING

Size: 5L

#### HEALTH AND SAFETY

Flammable flashpoint >40°C, refer to full Health and Safety data sheet, available on request.

#### TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact Thompson's Technical Service.

**IMPORTANT NOTE** The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Thompson's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Thompson's sole warranty is that the product will meet the Thompson's sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Thompson's specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Thompson's disclaims liability for any incidental or consequential damages