

# NON SLIP TILE ADHESIVE

**Thompson's Non Slip Tile Adhesive is an acrylic non-slip tile adhesive formulated to have excellent grab and non slip properties.**



## THOMPSON'S NON SLIP TILE ADHESIVE:

- Contract grade acrylic tile adhesive
- Ideal for showers, bathrooms & kitchens
- Excellent grab properties & high strength bond
- Mould resistant
- Conforms to BS EN 12004 D1T

## TECHNICAL DATA

Form	Viscous ready to use thixotropic paste
Storage Life	12 Months stored between 5°C and 25°C in original containers and protect from frost

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Thompson's Sales Representative prior to writing specifications on this product.

## SURFACE PREPARATION

Surfaces to be tiled must be sound, clean, dry and free of any contamination which might impair the adhesive bond.

Very porous or dusty surfaces and polished plaster should be sealed with a coat of Thompson's Universal PVA diluted as recommended. The sealer coat should be fully dry before tiling commences. Existing glazed tile surfaces should be roughened with an abrasive disc.

## APPLICATION

Apply with a notched spreader, for example, one with 6mm x 6mm notches at 25mm centres, to produce parallel ribs of adhesive onto which dry tiles should be applied. Apply the adhesive to cover an area of approximately 20 minutes working time (0.5m<sup>2</sup> - 1m<sup>2</sup>). Bed the tiles into the adhesive using a twisting action to ensure complete contact between the tiles and adhesive. The "SPOTTING" method of fixing should not be used. If necessary insert plastic spacers between tiles to allow at least 2mm wide grout lines.

Remove any excess adhesive from the face of the tiles with a damp cloth within 20 minutes of application. Leave tiles for at least 24 hours (48 hours if tiling on non-porous surfaces) before grouting.

## COVERAGE

Approximately 0.8m<sup>2</sup> per 1kg when using a notched trowel. This will fix 32 x 15 x 15cm tiles.

## CLEANING

Tools and any excess or spilt adhesive should be cleaned with water before it dries.

## PACKAGING

Sizes: 3.75kg, 7.5kg & 15kg

## LIMITATIONS

Thompson's Non Slip Tile Adhesive should not be used on surfaces which are subject to movement or flexing, external surfaces, swimming pools or for fixing floor tiles.

## HEALTH AND SAFETY

Thompson's Non Slip Tile Adhesive is essentially non hazardous in normal use. Avoid prolonged contact with skin. For further information please refer to Health and Safety data sheets available on request.

## TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact Thompson's Technical Service.

**IMPORTANT NOTE** The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Thompson's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Thompson's sole warranty is that the product will meet the Thompson's sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Thompson's specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Thompson's disclaims liability for any incidental or consequential damages.