

EPOXY PATCHING MORTAR



Thompson's Epoxy Patching Mortar is a three part general purpose epoxy mortar that makes tough and permanent repairs to damaged concrete, screeds, brick, steel and stone.

THOMPSON'S EPOXY PATCHING MORTAR

- Three part patching mortar
- Easy to use
- Ideal for repairing floors, steps and kerbs

TECHNICAL DATA

Form	Light coloured mortar
Storage Life	12 Months unopened stored between 5°C and 25°C in original containers
Mix Density	1.5
Application Thickness	Minimum 3mm Maximum 100mm
Recommended Application Temperature	+5°C to +25°C
Service Temperature	-30°C to +45°C
Open (Working) Time	45 minutes at 20°C
Initial Cure	24 Hours
Full Cure	7 Days

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Thompson's Sales Representative prior to writing specifications on this product.

SURFACE PREPARATION

Surfaces should be free from dust, loose materials and all traces of laitance, oil and grease.

APPLICATION

Remove the two containers and bag of filler from the bucket. Mix thoroughly the resin and hardener in the empty bucket. Use some of this mixture to sparingly prime the surface to be repaired.

Once the surface is primed add the filler to the resin mixture, mixing well until a cohesive texture is achieved. Trowel this mixture into the repair, compacting well. The trowel can be moistened with clean water to aid smoothing of the surface.

Very low temperatures will delay set. Use mixed materials within 45 minutes.

COVERAGE

Coverage 1.25m² per 5kg pack at 3mm thickness.

CLEANING

The mortar can be removed from equipment with warm soapy water.

PACKAGING

Size: 5kg

HEALTH AND SAFETY

Thompson's Epoxy Patching Mortar contains liquid epoxy resin and polyamine compounds. Please refer to Health and Safety data sheets available on request.

TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact Thompson's Technical Service.

IMPORTANT NOTE The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Thompson's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Thompson's sole warranty is that the product will meet the Thompson's sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Thompson's specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Thompson's disclaims liability for any incidental or consequential damages.