Thompson's®

PRODUCT DATA SHEET

WINDOW & DOOR FRAME SEALANT

Thompson's Window & Door Frame Sealant is a clear silicone rubber sealant for external sealing around door and window frames, including PVC-U.

THOMPSON'S WINDOW & DOOR FRAME SEALANT:

- Highly flexible
- · Immediately waterproof
- · Won't crack or peel

PACKAGING

Thompson's Window & Door Frame Sealant is available in 310ml cartridges packed in boxes of 12.

BEFORE YOU START

Use a stiff brush to get rid of any dust, dirt or loose material

APPLICATION

- Cut the nozzle at a 45° angle to a width matching the gap you're going to seal
- · Fit the cartridge into a standard sealant gun
- · Apply slowly and evenly at an angle to the repair, making sure it covers both sides of the repair
- · Smooth down with a wetted round spatula
- The product may remain tacky for a few hours after application

WISE PRECAUTIONS

Always read instructions carefully before use

LIMITATIONS

Thompson's Window & Door Frame Sealant cannot be overpainted. This product should not be applied to building materials that bleed oils, plasticisers, or solvents.

Thompson's Window & Door Frame Sealant silicone skins over rapidly and cures to a flexible rubber seal. Excess material should be cleaned up immediately using white spirit. Cured material can be removed using Geocel Silicone Sealant remover.

HEALTH AND SAFETY

Health and Safety data sheets available on request.

TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact Thompson's Technical Service.

IMPORTANT NOTE The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Thompson's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Thompson's sole warranty is that the product will meet the Thompson's sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Thompson's specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Thompson's disclaims liability for any incidental or consequential damages.

Sherwin-Williams Diversified Brands Ltd has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Sherwin-Williams Diversified Brands Ltd. operate an Environmental Management System that complies with the requirements of BS 7750:1994, Certificate No. EMS 35924. Sherwin-Williams Diversified Brands Ltd. has achieved Investors in People certification, (certificate number 59586).

©Sherwin-Williams Diversified Brands Ltd, Thorncliffe Park, Chapeltown, Sheffield S35 2YP

Tel: (0114) 240 9469 (Technical Services) (0114) 246 7171 (Main Switchboard) Fax: (0114) 245 5629 Email: enquiry@thompsonsweatherproofing.co.uk Web: www.thompsonsweatherproofing.co.uk

Thompsons is a Registered Trademark of the Sherwin-Williams Company. JANUARY, 2009 ISSUE 1





CI/Sfb: Yt4 April 2016